



## **E-Z WALL BASE**

- DESCRIPTION:** California Stucco E-Z Wall is an pre-blended cement BASE product containing Portland Cement, chopped glass fiber strands, silica sand and proprietary modifiers. It serves as an excellent base for all California Stucco finish products. E-Z Wall is designed to reduce the effects of shrinkage cracks.
- USES:** California Stucco E-Z Wall can be applied over clean, sound, unpainted masonry, stucco, brick or block or applied over a sound substrate when stucco mesh is used.
- COVERAGE:** California Stucco E-Z Wall comes in a 90-lb bag. Each bag will cover 25 square feet at 3/8" or 20 square feet at 1/2".
- WORKING TIME:** Approximately 30 to 60 minutes depending on weather conditions.
- CURING TIME:** Approximately 7 days and should be moist cured for initial 48 hours after installation.
- SOLUBILITY:** California Stucco E-Z Wall Base should be cleaned from tools and equipment with water immediately after use.
- STORAGE:** Bags must be stored off the ground or floor, kept in a cool, dry area, protected from rain and other damaging agents.
- LIMITATIONS:** California Stucco E-Z Wall BASE should be applied only to frost-free and unfrozen surfaces above 40 degrees Fahrenheit. If ambient temperature should fall below 40 degrees Fahrenheit, weather protection must be provided.
- MIXING:** Mix one 90-lb bag of California Stucco E-Z Wall BASE with 1-1/2 gallons of water in a power mixer for at least 15 minutes to insure proper hydration. If hand mixed, allow 15 minutes slack time, remix and apply.